

The SUNRNR SUN110, our flagship model, offers:

#### Rechargeable Battery

8D AGM - over 2000 Whrs electricity (245 amp-hour)  
Solar panel and wind turbine/aux connector portals for charging

#### Power Inverter

Output: 110/120 VAC 60 Hz  
Modified sine wave output  
Max continuous power: 3,500 W  
Surge capacity (peak power): 7,000 W  
Digital LCD wattage power meter  
Power and fault LED indicators  
Low voltage alarm and shutdown  
Four standard AC plug outlets (US)

#### Solar Panel

Charge rate: 135 W/hr (bright sunlight)  
One panel included; second panel optional for faster charge rates  
30' cord with plug for easy connection to unit  
56"h x 26"w x 2"d; aluminum frame; 27 lbs

#### Charge Controller

30 amp over/undercharge protector  
LCD digital display: voltmeter, solar current ammeter  
Battery charger with status display lights

#### DC End

Rugged master on/off disconnect switch  
12V DC cigarette-lighter socket output  
Chargeable by other 12V DC supplies such as wind turbine or microhydro

#### Chassis

Steel enclosure for ruggedness and safety  
4" caster wheels for easy portability  
Sturdy handles for lifting  
28"l x 15"w x 30"h; 260 lbs

User's Manual included. One-year manufacturer's limited warranty.

Easy to use – "plug & play".

Expandable with second solar panel and/or power module options.

MSRP: \$3800.