

The SUNRNR SUN110, our flagship model, offers:

Rechargeable Battery

8D AGM - over 2000 Whrs electricity (245 amp-hour)
Solar panel and wind turbine/aux connector portals for charging

Power Inverter

Output: 110/120 VAC 60 Hz
Modified sine wave output
Max continuous power: 3,500 W
Surge capacity (peak power): 7,000 W
Digital LCD wattage power meter
Power and fault LED indicators
Low voltage alarm and shutdown
Four standard AC plug outlets (US)

Solar Panel

Charge rate: 130 W/hr (bright sunlight)
One panel included; second panel optional for faster charge rates
30' cord with plug for easy connection to unit
56"h x 26"w x 2"d; aluminum frame; 27 lbs

Charge Controller

30 amp over/undercharge protector
LCD digital display: voltmeter, solar current ammeter
Battery charger with status display lights

DC End

Rugged master on/off disconnect switch
12V DC cigarette-lighter socket output
Chargeable by other 12V DC supplies such as wind turbine or microhydro

Chassis

Steel enclosure for ruggedness and safety
4" caster wheels for easy portability
Sturdy handles for lifting
28"l x 15"w x 30"h; 250 lbs

User's Manual included. One-year manufacturer's limited warranty.

Easy to use – "plug & play".

Expandable with second solar panel and/or power module options.

MSRP: \$3800.