

SUNRNR Specifications

Rechargeable Battery

- 8D AGM – 2000+ Whrs electricity (245 amp-hr) (5+ yr life)
- Lightweight Li-Ion battery option – decreases weight by 50 lbs/kW; increases price by \$2000/kW
- Solar panel and wind turbine/aux charging portals
- Chargeable by other 12V DC supplies such as microhydro or charger

Power Inverter (not installed in Power Module)

- Output: 110/120 VAC 60Hz (4 standard 15amp plug outlets) or 220 VAC 50Hz (2 universal 30amp outlets)
- Modified sine wave output
- Max continuous power: 3,500 W
- Surge capacity (peak power): 7,000 W
- Digital LCD wattage power meter
- Power and fault LED indicators
- Low voltage alarm and shutdown

Solar Panel

- Kyocera KC130TM 130 W (20+ yr life)
- One panel included; second panel optional for faster charge rates
- 30' cord with plug for easy connection to unit
- 56" h x 26" w x 2" d; aluminum frame; 27 lbs

Charge Controller

- 30 amp over/undercharge protector
- LCD digital display: voltmeter, solar current ammeter
- Battery and charge status LEDs

DC End

- Rugged master on/off disconnect switch
- 12V DC cigarette-lighter socket output
- Quick-connect plug for Power Module option

Chassis

- Patented steel enclosure for ruggedness and safety
- 4" caster wheels for easy portability
- Sturdy handles for lifting
- 28" l x 15" w x 30" h; ~260 lbs

Power Module Option (Identical to SUN110/220 w/out inverter)

- Link to main unit to expand (double, triple, ...) electricity generation and storage

**User's Manual included. One-year manufacturer's warranty.
Easy to use – "plug & play". Silent. No gas required.**



SUNRNR and Solar Panel



Stores Renewable Energy



110 or 220 VAC Output



SUNRNR Unit with Power Module



SUNRNR of Virginia, Inc.
PO Box 102
Port Republic, VA 24471
540-234-0164

info@sunnr.com
www.sunnr.com

MSRP Prices:

SUN110 \$3800.
SUN220 \$3950.
SUNPWR \$2900.
SUNLilon quote